TROUBLESHOOTING _

The following chart is provided to help in diagnosing the probable source of simple troubles. You may be able to solve many of these problems rather quickly, but others may require the skills of a mechanical technician. In such a case, consult an authorized dealer for servicing.

Monitoring Beeper Coded Signals

CODED SIGNALS	POSSIBLE CAUSE	REMEDY
4 short beeps	Shifter not in neutral.	Place shifter in neutral. Two short beeps will confirm neutral position.
1 long beep	Bad connection	Reinstall safety lanyard cap correctly over switch.
	 Uncoded safety lanyard 	Use only coded safety lanyard.
	Safety lanyard	Use another coded safety lanyard or refer to an authorized dealer.
8 short beeps	Micro-processor.	Refer to an authorized dealer.
Continuously beeps	Engine overheat	Refer to Engine Overheats below

ENGINE WILL NOT START

ENGINE WILE NOT OTALL		
OTHER OBSERVATION	POSSIBLE CAUSE	REMEDY
Engine does not turn over and the monitoring beeper sounds	Refer to monitoring beeper coded signals above.	
Engine does not turn over	Safety lanyard removed Burnt fuse Discharged batteries Battery connections, corroded or loose Water flooded engine	Install cap over switch. Check wiring then replace fuse. Refer to an authorized dealer. Refer to an authorized dealer. Refer to Submerged Jet Boat in SPECIAL PROCEDURES.
Engine slowly turns	 Discharged or weak batteries 	Refer to an authorized dealer.
Engine turns over	Fuel tank empty or water-contaminated Fuel filter clogged or water-contaminated Fuel flooded engine: Fouled spark plugs Misuse of choke	Refill. Syphon and fill with fresh fuel. Clean, check fuel tank for water. Replace. Use only with cold engine. Replace spark plugs.

ENGINE MISFIRES, RUNS IRREGULARLY

ENGINE MISTIRES, ROMS IRREGULARLY			
OTHER OBSERVATION	POSSIBLE CAUSE	REMEDY	
Weak spark	Fouled worn spark plugsFaulty RPM limiterToo much oil supplied to engine	Replace. Refer to an authorized dealer. Improper oil pump adjustment, refer to an authorized dealer.	
Lean fuel mixture	Fuel: Level too low, stale or water-contaminated Fuel filter, clogged or water-contaminated	Syphon and / or refill. Refer to an authorized dealer.	
Rich fuel mixture (high fuel consumption)	Flame arrester dirty / clogged Partially closed choke	Clean or replace. Refer to an authorized dealer.	